

CEYTREYLER TECHNICAL SPECIFICATIONS

MATERIALS		UNIT	50 CBM SCRAP TIPPER	
	Manufacturer	Ceytech Makine San. Ve Tic. A.S		
	Volume	50 m³		7.450kg
	Floor	5mm	HB450	
	Side walls (2 pcs.)	4mm/ 3mm	HB450/S700	
	Front wall	4mm	HB450	
	Rear door	3mm	S700	
	Chassis	Formed by high strength S700 steel welded in submerged arc welding robots.		
	FEATURES	King pin	2 " Sized flange type screwed from underneath/JOST	
Balance leg		Dual speed mechanical jack with 24 ton dynamic 50 ton static lifting capacity, LT ALU leg		
Undercarriage		3 axles with 9 ton capacity SAF Disc 430 CD Type Axle		
Suspension		SAF 6 air suspension/ 1 front axel lifting		
Brake System		Dual circuit pneumatic WABCO EBS brakes according to EEC standards.Load balancing distribution valve, Automatic brake adjustment arms with emergency brake system. Raise to adjust level- Lower valve. All valves are."WABCO" brand. Brake ratchets are automatic./ With a dual-circuit pneumatic compliance with EU regulations, a WABCO EBS 4S/2M braking system		
Wheels		6	385x65 R 22,5 Bridgestone/Pirelli/Lassa Tubeless tires.	
			6 x Steel Rims ET120/ 11.75X22.5	
Electric System		The electrical system includes park and warning lights on both sides along with a park,signal,stop and plate lights at the rear/ 7 and 15 ASPOCK electrical systems and lighting projectors in accordance with EU regulations		Aspöck
		2 x LED headlights rear/Reverse light		
		2 x LED spotlights on the landing gear		
Hyrdaulic system	Telescopic cyclinder that is a sinlge action C type HYVA Branded/ Cold draft hydraulic lift, direction control, and level valve HYVA			
ACCESSORIES	"E37" documented reflectors			
	1x PVC Tool Box			
	Red Strip reflector			
	Mudguards			
OPTIONS	Hydraulic Rear Door			
	No Tarpaulin			
	KTL Chassis			
SURFACE	Paint			
	Colour	Gray		

